

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.



#4

367.40946X00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: J. BOAKES, et al

Serial No.: 10/022,332

Filing Date: December 20, 2001

For: CONNECTOR

Attention: Box Missing Parts

LETTER CLAIMING RIGHT OF PRIORITY

Assistant Commissioner
for Patents
Washington, D.C. 20231

March 15, 2002

Sir:

Under the provisions of 35 USC 119 and 37 CFR 1.55, applicants hereby claim the right
of priority based on:

Great Britain Application No. 0031366.8
Filed: December 21, 2000

A Certified copy of said application document is attached hereto.

Respectfully submitted,

Carl I. Brundidge
Registration No. 29,621
ANTONELLI, TERRY, STOUT & KRAUS, LLP

CIB/jdc
Enclosures
703/312-6600



INVESTOR IN PEOPLE




The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed 
Dated 5 December 2001

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

PAT00037GB

2. Patent application number *
(The Patent Office will fill in this part)

21 DEC 2000

21 DEC 2000

0031366.8

3. Full name, address and postcode of the or of each applicant (underline all surnames)

NOKIA MOBILE PHONES LIMITED
KEILALAHDENTIE 4
02150 ESPOO
FINLAND

Patents ADP number (if you know it)

05911995004

If the applicant is a corporate body, give the country/state of its incorporation

FINLAND

4. Title of the invention

A CONNECTOR

5. Name of your agent (if you have one)

NOKIA IPR DEPARTMENT
NOKIA HOUSE
SUMMIT AVENUE
FARNBOROUGH
HAMPSHIRE
GU14ONG UK

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Patents ADP number (if you know it)

7577638001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

VFS

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description	12
Claim(s)	2
Abstract	1
Drawing(s)	6

10. If you are also filing any of the following,
state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right
to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination
and search (*Patents Form 9/77*)

1

Request for substantive examination
(*Patents Form 10/77*)

Any other documents
(*please specify*)

11.

I/We request the grant of a patent on the basis of this application.

Signature

HELEN HAWS

Date

19.12.2000

12. Name and daytime telephone number of
person to contact in the United Kingdom

EAN DAVIES 01252 865390

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

A CONNECTOR

This invention relates to an electrical connector. It finds particular, although
5 not exclusive use in connectors for removable data cards, such as SIM cards
in portable telephones. Other removable data cards include electronic
payment cards, and data storage cards such as SD or MMC cards.

Portable telephones operating according to the GSM communication
10 standard, amongst other standards, require the user to insert a SIM
(Subscriber Identity Module) card before a communication link can be
established with a host network. The SIM card is a type of so-called smart
card, and has an embedded integrated circuit which contains information
specific to a particular user, and enables him to access a communication
15 network. Without a SIM cards, a portable telephone can generally only be
used for emergency calls to a pre-defined number.

The SIM card has on its surface a number of discrete contact regions. These
regions are planar conductive areas which internally connect with the
20 embedded integrated circuit. Each region is insulated from its neighbours, and
is intended to be contacted by a suitable reader forming part of a host device,
such as a portable telephone. Typically, contact between the reader of the
host device and the card has been effected using sprung metal contacts
which are resiliently biased to contact respective regions of the SIM card.

25 An example of a connector suitable for use as a SIM card reader is shown at
Figure 1 of the accompanying drawings. The connector 100 comprises a body
portion 110 composed of an insulating plastics material. The body portion
houses a number of electrical connectors. On the upper surface of the body
portion are six sprung electrical contacts 120 arranged to make contact with
30 the conductive regions of a SIM card. These are either electrically connected

to, or integrally formed with, respective contacts 130 for mounting the connector 100 on a circuit board. Each contact 130 is soldered to, and makes contact with, a trace on a printed circuit board (PCB).

- 5 In order to ensure a reliable connection between the SIM card and the contacts 120, a constant pressure needs to be applied to ensure that contact is maintained between the contacts of the SIM card, and the contacts 120 of the connector 100.
- 10 The required contact pressure may be applied in a number of ways. Some solutions require a carriage for holding the SIM card, which can be locked into position over the connector. However, a simple approach is illustrated in Figure 2a, and in more detail in Figure 2b.
- 15 Figure 2a shows a photographic representation of the SIM card reader from a Nokia ® 6210 portable telephone. Figure 2b shows a detailed schematic view of the reader.

20 The SIM card reader of Figure 2b comprises a cut away region 200 which receives a SIM card. The lower right hand corner of the cut away region has an orientation feature 220 which permits the SIM card to be inserted only one way.

25 A SIM card may be inserted by positioning its left hand edge under the projection 210. The projection 210 secures the card in position along its left hand edge. The right hand edge of the card is then lowered into the cut away region 200, covering the connector 100. To secure the SIM card in position, the sliding catch 230 is moved to the left so that the SIM card is held in position by a combination of the projection 210 and the catch 230.

30

The catch is simply a shaped metal part which is secured to run in a channel defined by projections 240.

Contact is then ensured, as the downward pressure provided by the card reader keeps the card in contact with the resilient contacts 120 of the connector 100.

- 5 In addition to SIM cards, portable devices are increasingly being provided with other removable memory devices. Examples of these include electronic payment cards for use with e-commerce or m-commerce (electronic or mobile commerce). In such systems, the user is able to pay for a purchase using an electronic payment card which may allow payment to be taken from his bank
10 account or credit card account for instance.

- Further, the increasingly multimedia nature of portable radiotelephones, e.g. the addition of digital camera capabilities, music playback facilities or video playback capabilities, means that large amounts of data must be generated or
15 read locally. To this end, high capacity data storage cards are provided, which may be removably connected to the portable device. As an example, a portable telephone with a camera function may be able to take a photograph, and choose to either store the image locally on a data storage card, or send it via the communication network to another user. If the image is stored locally,
20 the user can remove the card containing the image data, and transfer the data from the card to his PC for instance.

- The height of the connector shown in Figure 1 is of the order of 2.7mm. The height of the SIM card itself is 0.8mm. These two dimensions, combined with
25 the retaining means required, such as the sliding catch 230 of Figure 2b, can result in a total height of approximately 5 or 6mm for the SIM card reader. The increasing miniaturisation of portable telephone devices makes it increasingly difficult to accommodate the one or more removable memory devices required, and described above.

In particular, it is generally not practicable to reduce the size of existing connectors further as the contacts 120 become more prone to damage the smaller they become.

5 According to a first aspect of the present invention, there is provided an electrical connector for connection to a mating connector comprising a substrate supporting a contact for making electrical connection with a corresponding contact on the mating part, wherein the contact of the electrical connector is a resiliently deformable hollow projection

10

Advantageously, the connector may comprise several contacts so that a complete multi-pole connector may be provided.

Preferably, the contact of the connector is generally dome-shaped, i.e. it is
15 hollow and has one generally convex exterior face, and a generally concave interior face.

The substrate on which the contacts may be mounted is preferably a flexible PCB, although a rigid PCB may also be employed.

20

The substrate preferably carries tracking for connecting the contacts to further circuitry in a host device.

The contacts may advantageously be attached to the substrate through use of
25 a suitable solder or glue.

In order to ensure a reliable connection with the mating part, the connector preferably includes means for retaining the mating part in electrical contact with the reader.

30

Preferably, such means for retaining the mating part in reliable contact does not greatly increase the volume occupied by the connector. A suitable

retaining device is a simple sliding catch operable to hold the mating part in location.

5 The contacts are preferably made from a metallic material as this has the desired conductive and resilient properties. However, it is possible that the contacts are composed of an insulating material, such as a plastics material, coated with a suitable conductive material.

10 Preferably, the contact is permanently connected to a conductive track on the substrate for further connecting the contact to associated circuitry.

15 In an advantageous embodiment, the connector can be configured to comprise a contact, or contacts, on each of two opposing surfaces of the substrate. In this way, the connector can be used for making contact with two mating parts simultaneously. This arrangement offers the benefit that the volume occupied by such an arrangement is only marginally greater than that occupied by the mating parts in isolation.

20 A beneficial use for the connector is as a smart card reader, where the smart card has its contacts disposed in a planar fashion on one or more of its surfaces.

25 A particular type of smart card benefiting from the invention is the so-called SIM card used in portable telephones.

For a better understanding of the present invention, and to understand how the same may be brought into effect, the invention will now be described, by way of example only, with reference to the appended drawings in which:

30 Figure 1 shows a prior art electrical connector used for making electrical connection to a smart card;

Figure 2a shows a pictorial representation of a prior art SIM card reader from a portable telephone;

Figure 2b shows a detailed schematic view of the reader of Figure 2a;

5

Figure 3a shows a plan view of a SIM card reader according to an embodiment of the invention;

Figure 3b shows a sectional view of the SIM card reader of Figure 3a;

10

Figure 4 shows the card reader of Figure 3 in-situ in a portable telephone;

Figure 5 shows an alternative card-reader configuration;

15

Figure 6a shows a configuration capable of reading two cards simultaneously;

Figure 6b shows an alternative configuration capable of reading two cards simultaneously;

20

Figure 7a shows a plan view of a twin card reader according to an embodiment of the invention; and

Figure 7b shows a cross sectional view of the card reader of Figure 7a.

25

Figure 3a shows a SIM card reader 300 in accordance with embodiments of the present invention. The reader comprises a substrate material 310 onto which are printed conductive traces 320. Mounted onto the substrate in correspondence with portions of the conductive traces are several conductive hollow domes 330 acting as contacts. The domes are made of a conductive

30

metal. An alternative composition for the domes is a plastics material coated with a conductive layer. The domes may be considered to be sections of a hollow sphere, somewhat smaller than a hemisphere in the present

embodiment. The domes in this embodiments are generally circular at their base, and generally concave. However, the contacts need not be dome shaped in order to function according to embodiments of the invention.

- 5 The hollow nature of the dome 330 provides the resilience needed to ensure that a reliable electrical connection is maintained. As the dome is depressed by the application of a force, e.g. when a SIM card is connected, the dome structure is elastically deformed. However, as soon as the force is removed, the dome structure returns to its stable equilibrium position. Provided that the
10 dimensions of the dome are chosen so as to minimise the effects of fatigue, many tens of thousands of such operations can be expected.

- The contacts can be seen to be free-standing and self-supporting i.e. they require no supporting structure. This is in contrast to the prior art connector of
15 Figure 1 which requires a relatively bulky insulating body portion 110 to provide structural integrity for the contacts. It would not be possible to simply remove the body portion of the prior art connector as the contacts would then be liable to short circuit, or be damaged in the absence of a supporting structure. Embodiments of the invention, by removing the need for such a
20 body portion, greatly decrease the volume occupied by the connector.

- The inherently stable shape of the dome contact offers advantages in that the individual domes may be easily placed on the flexible PCB 310 by automated machinery. However, other shapes of contacts would function adequately,
25 and may be used according to embodiments of the invention. For instance, contacts having a non-circular outline, e.g. elliptical, could be used. Another alternative is the use of a hollow semi-cylindrical shaped contact with open ends, which would enjoy the same resilient property as the dome.

- 30 Figure 3b shows a sectional view of reader 300 along the line A-A. This clearly shows the domes 330 mounted on the substrate 310.

The substrate material is a flexible insulating material, such as is usually used in the manufacture of flexible PCBs. Printed onto the substrate in the usual way are a number of conductive traces. The traces run from one end of the substrate, where they provide contact pads 340 for connection to a connector
5 for connecting the reader 300 to a PCB. At the opposite end to the contact pads 340, the traces terminate in a circular trace. The circular trace corresponds in size to the outline of the metal domes 330 which are attached to the substrate 310. The domes may be attached by a number of means such as by soldering or by use of a conductive glue.

10

The circular trace matching the circumference of the domes is only one possible trace configuration. The trace may consist of one or more discrete points lying on the circumference of the circle, or the circular trace may be filled.

15

Once assembled, the reader 300 may be fitted into the host apparatus, such as a portable telephone. This is achieved through use of a connector, fitted to the contact pads 340, mating with a corresponding connector in the host apparatus. Alternatively, the reader may be permanently connected to the
20 host apparatus by forming it as part of a PCB of the host apparatus, for instance.

Figure 4 shows the reader 300 positioned in a host apparatus - in this case, a portable telephone. The main circuit board 400 of the telephone supports all
25 the major components of the device. In particular, it accommodates the main processor, display driver, audio circuitry and RF circuitry. The RF circuitry is located inside a screened metal can 410. This prevents any stray RF signals interfering with other signals in the device.

30 Mounted on the surface of the can 410 is the SIM card reader 300. The domes 330 are oriented away from the can. The other end of the reader 300 terminates in a connector 420 which couples the reader to the circuit board

400, and thus to the processor of the telephone, enabling the SIM card to be accessed.

5 The SIM card 500 is located in a recess in a cover 430 of the telephone. It is held in place in the recess through use of a small sprung clip 440. Alternative means of holding it in place are possible. For instance, a sliding catch arrangement similar to that shown in Figures 2a and 2b could be used to secure the SIM card in position.

10 Once the SIM card is secured in the recess, it is brought into contact with the reader simply by attaching the cover 430 to the telephone. The cover may be attached in any convenient manner provided that a firm attachment is achieved. For instance, a known techniques of attaching a telephone cover is a sliding connection including latches to firmly grip the cover. Alternatively, the
15 cover may be attached with screws or other retaining devices. This technique is more suitable for situations where regular changing of the SIM card, or similar smart card, is not required.

Once the card 500 is securely brought into contact with the reader 300, the
20 domes 330 contact the respective regions of the SIM card, enabling an electrical connection between them to be established. Since the domes are hollow metal domes, they are resilient. This enables the domes to be almost completely flattened against the substrate if a sufficient force can be applied. The result of this is that the space taken up by the reader becomes almost
25 negligible. The entire SIM card and reader arrangement in use is barely thicker than the thickness of the SIM card combined with the substrate 310 of the reader. For clarity, Figure 4 shows a larger gap between the SIM card and the substrate than could be achieved in practice.

30 Once the cover containing the SIM card is removed, the domes 330 spring back into their normal rest positions as shown in Figure 3b.

The reader 300 does not need to be mounted on the screened can 410 as shown in Figure 4. Instead, the reader may be completely integrated onto the main telephone printed circuit board 400. This configuration is shown at Figure 5. Like numerals refer to like features. Again, the gap between the SIM
5 500 and the substrate (in this case the circuit board 400) has been exaggerated for clarity.

In an enhancement of the present invention, a SIM card reader is presented which is capable of reading two SIM or other smart cards. There is a need for
10 portable telephones to be able to access more than one set of information stored on different cards. For instance, in the application of m-commerce (mobile commerce), the user may wish to purchase an item direct from his telephone. To do this, he may need to insert a payment card into the telephone so that its stored details may be sent to the merchant's system at
15 the other end of a communication link. It is envisaged that the payment card will be a smart card resembling closely the SIM card currently used in portable telephones.

In another configuration, it may be desirable to install two SIM cards, each
20 one corresponding to a different network account with a different network provider. In this way, the user has access to more than one telephone account from a single telephone.

It is therefore desirable for the telephone to be able to accept and access
25 more than one smart card at any given time.

Providing two prior art card readers may prove to use a prohibitive amount of scarce volume in a portable radio telephone. By providing two card readers as described below, it is possible the space occupied is comparable to that
30 occupied by a single prior art card reader.

Figure 6a shows a substrate 310' having conductive domes 330 mounted on opposing surfaces. In this way, two SIM cards may be positioned as shown - one on each side of the reader. In this case, the substrate 310' may be made of a more rigid material than the flexible PCB used in the previous embodiment. Alternatively, the flexible PCB 310 of the previous embodiment may be fitted into a more rigid frame structure to provide the required rigidity.

Figure 7a shows a plan view of the reader according to this embodiment of the invention. Figure 7b shows a cross-sectional view along line B-B. The reader is situated in the internal structure 600 of the portable telephone. A recess 610 is located in the structure for accommodating a first SIM card. Connected to the body 600 at hinge 640 is the reader of Figure 6a. This comprises the substrate 310', surrounded by a relatively rigid frame 630. The frame and substrate hinge as shown in Figure 7b so that the first SIM card may be inserted into the recess. Once inserted, the frame is lowered over the card, and catch 620 is slid across to maintain contact pressure between the reader and the card.

Once the first card is stowed in the recess, the second set of domes are left exposed on the top surface of the reader. It is with these domes that the second card (either a SIM card or another form of smart card) will make contact. The connection of the second card can be achieved as described in the first embodiment. i.e. a recess can be provided in another housing of the telephone, e.g. the rear housing, so that once attached, the card makes a reliable contact with the reader.

A benefit of such a structure, using a relatively rigid substrate 310' or frame 630, is that the reader is capable of operating with a single card in either one of the two available slots.

Use of the card reader of Figure 6b may be desirable in some situations, but it requires the use of a dummy card to maintain contact pressure if only a single card is in use.

- 5 Although described in terms of application to a reader of smart cards, particularly SIM cards, the skilled man would immediately realise that the connector herein described could be used in any situation requiring an electrical connector capable of making contact with a suitable mating part. Examples might include any type of removable or semi-permanent plug-in
10 card.

The present invention includes any novel feature or combination of features disclosed herein either explicitly or any generalisation thereof irrespective of whether or not it relates to the claimed invention or mitigates any or all of the
15 problems addressed.

CLAIMS

1. An electrical connector for connection to a mating connector comprising a substrate supporting a contact for making electrical connection
5 with a corresponding contact on the mating part, wherein the contact of the electrical connector is a resiliently deformable hollow projection.
2. A connector as claimed in claim 1 wherein an exterior surface of the contact is generally convex.
10
3. A connector as claimed in claim 1 or 2 wherein the contact is generally dome-shaped.
4. A connector as claimed in any one of the preceding claims wherein the
15 contact comprises a metal.
5. A connector as claimed in any one of claims 1 to 3 wherein the contact comprises an insulating material treated so as to be conductive.
- 20 6. A connector as claimed in any one of the preceding claims wherein the substrate comprises a Printed Circuit Board (PCB).
7. A connector as claimed in claim 6 wherein the PCB is flexible.
- 25 8. A connector as claimed in any one of the preceding claims wherein the substrate supports a conductive track electrically coupled to the contact.
9. A connector as claimed in any one of the preceding claims including
30 means for retaining the mating part in contact with the connector.

10. A connector as claimed in any one of the preceding claims wherein the contact is secured in position on the substrate using solder.
11. A connector as claimed in any one of the preceding claims wherein the
5 connector comprises a plurality of contacts.
12. A connector as claimed in any one of the preceding claims wherein the substrate supports a contact on each of two opposing surfaces of the substrate.
- 10 13. A connector as claimed in claim 12 wherein the connector is arranged to make contact with two mating parts arranged on opposing sides of the substrate.
- 15 14. A connector as claimed in claim any one of the preceding claims wherein the connector is for use as a smart card reader
15. A connector as claimed in claim 14 wherein the smart card is a SIM card for use with a portable telephone.
- 20 16. A portable telephone comprising a connector according to any one of the preceding claims.
17. A connector substantially as herein described, having particular
25 reference to Figures 3 to 7 of the accompanying drawings.

ABSTRACT

An electrical connector is disclosed. The connector has a substrate supporting a contact for making electrical connection with a corresponding contact on a mating part. The contact of the electrical connector is a resiliently deformable
5 hollow projection. The connector finds particular use as a smart card reader.

Figure 3a, 3b.




Figure 1
PRIOR ART




Figure 2a
PRIOR ART




Figure 2b
PRIOR ART




Figure 3a




Figure 3b




Figure 4




Figure 5




Figure 6a




Figure 6b




Figure 7a




Figure 7b